

Mobilgard HSD 20W-50

ExxonMobil Marine, Vietnam

Product Description

Mobilgard HSD 20W-50 is a high-speed diesel (HSD) lubricant for a range of marine applications. Mobilgard HSD 20W-50 is a high performance, heavy duty engine oil that provides proven protection to diesel engines operating in severe applications. It is recommended by ExxonMobil for use in a wide range of heavy duty applications and marine operating environments.

Features and Benefits

The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Control sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engine and longer engine life
Stay-in-grade shear stability	Help reduce oil consumption and wear

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading engine manufacturers
- Older and reconditioned marine engines
- Engines that meet API CF-4/CF/SG/SF

Specifications and Approvals

Mobilgard HSD 20W-50 is recommended for use in applications requiring:

API CF-4

APICF

Properties and Specifications

Property	
Grade	SAE 20W-50

Property	
Kinematic Viscosity@40 C, mm ² /s, ASTM D445	148.9
Kinematic Viscosity@100 C, mm ² /s, ASTM D445	17.6
Ash, Sulfated, mass%, ASTM D874	1.0
TBN, mgKOH/g, ASTM D2896	8.4
Pour Point, °C, ASTM D97	-30
Flash Point, °C, ASTM D92	220
Density@15C, g/cm ³ , ASTM D4052	0.880

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @<http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2020

<http://www.exxonmobil.com>